FRONTMATEC



Optimizing the production flow

Lifting and tilting devices

Lifting and tilting device type 27000



Swing-Loader type 27100



- Lifting and controlled emptying of 200-300 l standard trolleys or special charging trays
- Lifting weight: Max 350 kg
 Material: Stainless steel, W.-no. 1.4301 with surface blasted by glass beads
- Options:
 - Special controls on request
 - Stationary or mobile version
 - Available with table and other attachments

- Lifting and controlled emptying of 200-300 I standard trolleys

- Lifting weight: Max 350 kg
- Material: Stainless steel, W.-no. 1.4301 with surface blasted by glass beads
- Options:
 - Adjustment for special containers possible
 - Tilting device available for higher lifting loads
 - Stationary or mobile design
 - On request with table or conveyor belt connection
 - Available with integrated weighing

Swing-Loader type 27200



- Lifting and controlled emptying of 600 I and 1000 I container or special charging trays
- Material: Stainless steel, W.-no.
 1.4301 with surface blasted by glass beads
- Options:
 - Special controls on request
 - Stationary or mobile version
 - Available with table and other attachments

Lifting, tilting and weighing device for bins/container

Batching station



- Lifting and controlled emptying of large containers, 200-300 I standard trolleys or special charging trays
- Digital weighing unit in standard for 200-300 I standard trolleys •
- Equipped with the required number of tilting stations
- Options:
 - Enlargement of the station by second weighing unit
 - Collecting channel for liquids
 - Additional buffer chute

Weighing device for trolleys 200/300 liters

Scales type 2760



- Weighing of 200-300 I standard trolleys or special charging trays
- Lifting weight: Max 350 kg
- Material: Stainless steel, W.-no. 1.4301 with surface blasted by glass beads
- Options:
 - Special controls on request
 - Stationary or mobile version
 - Higher loads possible on request

Trolleys and meatbins Charging trolleys according to DIN9797 up to 300 liters

Trolley type 2410



Trolley type 2410 - 200 I





Trolley - 200 I - with lid

- 200/300 I standard trolley
- Robust and stable
- Material: 2 mm stainless steel sheets, no. 1.4301
- Deep-drawn trolley base reinforced to a total of 5.0 mm .
- Electrolytically polished hygiene surface
- Options:
 - Wheels in individual colors
 - Perforated walls and floors
 - Pipe nozzle
 - Plastic lid made of polyethylene
 - Stainless steel lid with handle
 - Special designs on request

Contact

CN: shanghai@frontmatec.com Phone: +86 215 859 4850

DE: beckum@frontmatec.com Phone: +49 252 185 070

DK: kolding@frontmatec.com Phone: +45 763 427 00

ES: barcelona@frontmatec.com Phone: +34 932 643 800

NL: rijssen@frontmatec.com Phone: +31 886 294 000

RU: moscow@frontmatec.com Phone: +7 495 424 9559

UK: birmingham@frontmatec.com Phone: +44 121 313 3564

US: kansascity@frontmatec.com Phone: +1 816 891 2440

DEBEC_V1-0_2021_EN

